



Long Range Booster

LRB

The palm-size long range booster.
Small. Smart. And beyond splendid.



WiFi and Bluetooth connection with base receiver. Flexible and truly wireless.



Network connection via SIM card provides more possibilities for NTRIP users.




Make various configurations on webserver wirelessly.



7W small output delivers a long working distance up to 10-20km*¹ with stable and safe connection.



10h*² working time with internal battery and powerbank. Also supports ordinary accumulator.



Specifically tailored for STEC S-LINK protocol, and compatible to others.

1. Working distance differs in different conditions.
2. Powerbank of minimum 20,000mAh with fast charge.

SPECIFICATIONS

LRB



GENERAL

Frequency Range	410-470MHz
Operating Mode	Half-duplex
Channel	16 channels
Channel Spacing	12.5 KHz / 25 KHz
Air Rate	9,600bps, 19,200dps
Modulation	GMSK, 2FSK, 4FSK, LoRa
Operating Voltage	9-36 V
Power Consumption (@12V input)	Transmit (high): 17W Receive: 2.5W
Frequency Stability	≤1.0 ppm
Protocol	S-LINK, TrimTalk 450S, SATEL, etc.

TRANSMITTER

RF Output Power	3W / 7W (12V input)
RF Power Stability	±1.0 dB
Adjacent Channel Inhibition	>50 dB

RECEIVER

Sensitivity	<-118 dBm @ BER 10 ⁻⁵ , 9600 bps <-128 dBm @ S-LINK
Co-channel Inhibition	>-12 dB
Block	>70 dB
Adjacent Channel Selectivity	>52 dB @ 25KHz
Perturbation Resistance Stray	>55 dB

WIRELESS

4G Module	EG25
Supportable Bands	LTE-FDD: B1/B2/B3/B4/B5/B7/B8/B12/ B13/B18/B19/B20/B25/B26/B28 LTE-TDD: B38/B39/B40/B41 UMTS: B1/B2/B4/B5/B6/B8/B19 GSM: B2/B3/B5/B8
WiFi	IEEE 802.11 a/b/g/n/ac
Bluetooth	Bluetooth 5.0

INTERFACE

Radio Antenna Interface	TNC
4G Antenna Interface	TNC
Antenna Interface Impedance	50 ohm
Data Interface	Type-C USB, LEMO 5-pin

PHYSICAL

Battery	Internal Li-on battery, 3.6V 13,600mAh
Dimension	128mm*108mm*44mm
Weight	720g
Working Temperature	-40°C - +85°C
Storage Temperature	-45°C - +90°C
Water & Dust Proof	IP67



GUANGZHOU STAR INFORMATION TECHNOLOGY CO., LTD.
C-201 Yunsheng Science Park, No.11 Middle Guangpu Road, Huangpu District, Guangzhou 510663, China
sales@stecprecision.com support@stecprecision.com

